



Miller and Company LLC
9700 West Higgins Road
Suite 1000
Rosemont, Illinois 60018

Telephone Number: 847-696-2400

Updated: December 5, 2012

Product: Milco 18 GP Carbon Raiser

The subject product is a mechanical blend of the following ingredients:

Component

Milco 15 Calcined Anthracite

Milco 16 Graphite

Custom blended to specification at time of blending.

Since the mixture presents no greater hazard than any of the individual components, the Material Safety Data Sheets for the individual components are attached and satisfy the requirements of the data sheet for the mixture (Appendix A, Clarifications and Interpretations for the Hazard Communication Standard (HCS), OSHA CPL 2-2, 38B, 15 August 1988).

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MDL INFORMATION SYSTEMS, INC.
 1281 Murfreesboro Road, Suite 300
 Nashville, TN 37217-2423
 1-615-366-2000

EMERGENCY TELEPHONE NUMBER:
 1-800-424-9300 (NORTH AMERICA)
 1-703-527-3887 (INTERNATIONAL)

SUBSTANCE: CALCINED ANTHRACITE COAL

TRADE NAMES/SYNONYMS:

COAL, ANTHRACITE, CALCINED; CALCINED ANTHRACITE; DEVOLATIZED ANTHRACITE; COAL DUST; COAL CALCINATE; OHS35039

CHEMICAL FAMILY: polynuclear, aromatic, hydrocarbons

CREATION DATE: Apr 20 1993

REVISION DATE: Oct 31 2007

SECTION 2 COMPOSITION, INFORMATION ON INGREDIENTS

COMPONENT: CALCINED ANTHRACITE COAL
 CAS NUMBER: 68187-59-7
 EC NUMBER (EINECS): 269-111-1
 PERCENTAGE: 100.0

COMPONENT: QUARTZ
 CAS NUMBER: 14808-60-7
 EC NUMBER (EINECS): 238-878-4
 PERCENTAGE: >1

SECTION 3 HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4): HEALTH-1 FIRE-1 REACTIVITY-0

NFPA

EC CLASSIFICATION (CALCULATED): Not determined.

EMERGENCY OVERVIEW:

COLOR: black

PHYSICAL FORM: solid

MAJOR HEALTH HAZARDS: cancer hazard (in humans)

PHYSICAL HAZARDS: Dust/air mixtures may ignite or explode.

POTENTIAL HEALTH EFFECTS:

INHALATION:

SHORT TERM EXPOSURE: irritation


LONG TERM EXPOSURE: difficulty breathing, bluish skin color, lung damage, cancer

SKIN CONTACT:

SHORT TERM EXPOSURE: irritation

LONG TERM EXPOSURE: no information is available

EYE CONTACT:



SHORT TERM EXPOSURE: irritation

LONG TERM EXPOSURE: no information on significant adverse effects

INGESTION:

SHORT TERM EXPOSURE: no information on significant adverse effects

LONG TERM EXPOSURE: no information is available

CARCINOGEN STATUS:

OSHA: N

NTP: Y

IARC: Y

SECTION 4 FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.

SKIN CONTACT: Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

EYE CONTACT: Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

INGESTION: If a large amount is swallowed, get medical attention.

SECTION 5 FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Slight fire hazard. Dust/air mixtures may ignite or explode.

EXTINGUISHING MEDIA: regular dry chemical, carbon dioxide, water, regular foam

Large fires: Use regular foam or flood with fine water spray.

FIRE FIGHTING: Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Dike for later disposal. Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

SECTION 6 ACCIDENTAL RELEASE MEASURES

WATER RELEASE:

Subject to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). Keep out of water supplies and sewers.

OCCUPATIONAL RELEASE:

Large spills: Collect spilled material in appropriate container for disposal. Avoid generating dust. Clean up residue with a high-efficiency particulate filter vacuum.

SECTION 7 HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.
Keep separated from incompatible substances.

Use methods to minimize dust.

SECTION 8 EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE LIMITS:

CALCINED ANTHRACITE COAL:

COAL DUST:

- 2 mg/m³ OSHA TWA (respirable particulate) (<5% crystalline silica)
- 0.1 mg/m³ OSHA TWA (respirable particulate) (>=5% crystalline silica)
- 2 mg/m³ UK OES TWA (respirable dust)

MEASUREMENT METHOD: Particulate filter; Gravimetric; NIOSH IV # 0600,
Nuisance Dust (Respirable); ALSO # 7500

COAL DUST - ANTHRACITE:

- 0.4 mg/m³ ACGIH TWA (respirable particulate)

QUARTZ:

- 0.3 mg/m³ OSHA TWA (total particulate)
- 0.1 mg/m³ OSHA TWA (respirable particulate)
- 0.05 mg/m³ ACGIH TWA (respirable fraction)
- 0.05 mg/m³ NIOSH recommended TWA 10 hour(s) (respirable dust)
- 0.3 mg/m³ UK MEL TWA (respirable particulate)

MEASUREMENT METHOD: Particulate filter; Low-temperature ashing; X-ray
diffraction spectrometry; NIOSH IV # 7500; ALSO # 7601, # 7602

VENTILATION: Ventilation equipment should be explosion-resistant if explosive
concentrations of material are present. Provide local exhaust ventilation
system. Ensure compliance with applicable exposure limits.

EYE PROTECTION: Wear splash resistant safety goggles. Provide an emergency eye
wash fountain and quick drench shower in the immediate work area.

CLOTHING: Wear appropriate chemical resistant clothing.

GLOVES: Wear appropriate chemical resistant gloves.

RESPIRATOR: Under conditions of frequent use or heavy exposure, respiratory
protection may be needed. Respiratory protection is ranked in order from
minimum to maximum. Consider warning properties before use.
Any chemical cartridge respirator with organic vapor cartridge(s) and dust
and mist filter(s).
Any chemical cartridge respirator with organic vapor cartridge(s) and
high-efficiency particulate filter(s).
Any air-purifying respirator with a full facepiece, an organic vapor
canister and a dust, mist, and fume filter.
Any powered, air-purifying respirator with a full facepiece and a

high-efficiency particulate filter.

For Unknown Concentrations or Immediately Dangerous to Life or Health -
Any supplied-air respirator with full facepiece and operated in a
pressure-demand or other positive-pressure mode in combination with a
separate escape supply.
Any self-contained breathing apparatus with a full facepiece.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: solid
COLOR: black
ODOR: Not available
BOILING POINT: Not applicable
MELTING POINT: Not available
VAPOR PRESSURE: Not applicable
VAPOR DENSITY: Not applicable
SPECIFIC GRAVITY: Not available
WATER SOLUBILITY: Not available
PH: Not applicable
VOLATILITY: Not applicable
ODOR THRESHOLD: Not available
EVAPORATION RATE: Not applicable
COEFFICIENT OF WATER/OIL DISTRIBUTION: Not available

SECTION 10 STABILITY AND REACTIVITY

REACTIVITY: Stable at normal temperatures and pressure.

CONDITIONS TO AVOID: Avoid generating dust.

INCOMPATIBILITIES: oxidizing materials, metals, metal salts, halogens,
combustible materials, reducing agents, bases, acids

CALCINED ANTHRACITE COAL:

OXIDIZERS (STRONG): Fire and explosion hazard.

QUARTZ:

ALKALIES (STRONG): May be attacked.

CHLORINE TRIFLUORIDE: Possible explosion.

HYDROCHLORIC ACID: Exothermic reaction.

HYDROFLUORIC ACID: May be attacked.

MANGANESE TRIFLUORIDE: Violent reaction.

METALS: May produce violent explosion.

OXIDIZERS (STRONG): Fire and explosion hazard.

OXYGEN TRIFLUORIDE: Possible explosive reaction.

OZONE: Possible explosive reaction in presence of organic materials.

VINYL ACETATE: Vigorous reaction.

XENON HEXAFLUORIDE: Possible detonation.

COAL DUST:

OXIDIZERS (STRONG): Fire and explosion hazard.

HAZARDOUS DECOMPOSITION:

Thermal decomposition products: oxides of carbon

POLYMERIZATION: Will not polymerize.

SECTION 11 TOXICOLOGICAL INFORMATION

QUARTZ:

TOXICITY DATA:

16 mppcf/8 hour(s)-17.9 year(s) intermittent inhalation-human TCLO; 300 ug/m³/10 year(s) intermittent inhalation-human LCLO; 90 mg/kg intravenous-rat LDLo; 200 mg/kg intratracheal-rat LDLo; 40 mg/kg intravenous-mouse LDLo; >20 mg/kg intratracheal-mouse LD; 20 mg/kg intravenous-dog LDLo; 80 mg/m³/26 week(s) intermittent inhalation-rat TCLO; 108 mg/m³/6 hour(s)-3 day(s) intermittent inhalation-rat TCLO; 58 mg/m³/13 week(s) intermittent inhalation-rat TCLO; 1475 ug/m³/8 hour(s)-21 week(s) intermittent inhalation-mouse TCLO; 4932 ug/m³/24 hour(s)-39 week(s) continuous inhalation-mouse TCLO; 28 mg/m³/3 week(s) intermittent inhalation-guinea pig TCLO; 3 mg/m³/6 hour(s)-78 week(s) intermittent inhalation-hamster TCLO

CARCINOGEN STATUS: NTP: Known Human Carcinogen; IARC: Human Sufficient Evidence, Animal Sufficient Evidence, Group 1; EC: Category 2
Adenocarcinomas and squamous-cell carcinomas of the lung in rats were produced after inhalation or repeated intratracheal instillation of various forms of crystalline silica. Malignant lymphomas developed in rats after intrapleural and intraperitoneal injections of quartz suspensions and intrapleural injection of cristobalite and tridymite. Epidemiologic studies indicate lung cancer occurs more frequently among silicotics than in the general population.

ACUTE TOXICITY LEVEL: Insufficient Data.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: respiratory disorders

TUMORIGENIC DATA:

50 mg/m³ inhalation-rat TCLO/6 hour(s)-71 week(s) intermittent; 45 mg/kg intraperitoneal-rat TDLo; 90 mg/kg intravenous-rat TDLo; 90 mg/kg intrapleural-rat TDLo; 111 mg/kg intratracheal-rat TDLo; 100 mg/kg intratracheal-rat TDLo/19 week(s) intermittent; 900 mg/kg implant-rat TDLo; 4000 mg/kg implant-mouse TDLo; 83 mg/kg intrapleural-hamster TDLo; 90 mg/kg intraperitoneal-rat TD/4 week(s) intermittent; 450 mg/kg intraperitoneal-rat TD/4 week(s) intermittent; 4554 mg/kg implant-rat TD; 200 mg/kg intrapleural-rat TD; 100 mg/kg intrapleural-rat TD; 100 mg/kg intrapleural-rat TD; 100 mg/kg intrapleural-rat TD

MUTAGENIC DATA:

micronucleus test - human lung 40 ug/cm²; micronucleus test - hamster lung 160 ug/cm²

ADDITIONAL DATA: Smoking may enhance the toxic effects.

HEALTH EFFECTS:

INHALATION:

ACUTE EXPOSURE:

CALCINED ANTHRACITE COAL: May cause irritation.

QUARTZ: Exposure to high concentrations may cause physical discomfort of the upper respiratory tract.

CHRONIC EXPOSURE:

CALCINED ANTHRACITE COAL: Inhalation of anthracite coal dust for several

years may cause coal workers pneumoconiosis. Coal workers pneumoconiosis exists in 2 forms: Simple, which results from carbon particles alone, and complicated, from a mixture of particles resulting in progressive massive fibrosis. Simple pneumoconiosis is slow in onset with nonspecific symptoms including coughing, wheezing, dyspnea, and black sputum. Simple pneumoconiosis may occur concomitantly with chronic bronchitis and emphysema and is associated with minimal respiratory impairments. Diagnosis is made on the presence of small opacities on chest X-ray. As the simple pneumoconiosis progresses to an advanced stage, some reduction in ventilatory function may occur. Coal worker's pneumoconiosis appears to stop when exposure ceases, but progressive massive fibrosis may still develop. Complicated pneumoconiosis is diagnosed by large opacities on chest X-ray. Complicated pneumoconiosis is associated with reduction in ventilatory capacity, low diffusing capacity, abnormalities of gas exchange, low arterial oxygen tension, severe emphysema, pulmonary hypertension, right heart failure, and premature death. Tuberculosis and bacterial pneumonia are serious complications. Caplan's syndrome, depressed interferon activity, and cytotoxic effects have been reported. Freshness and increased surface area of dust particles increases cytotoxicity.

QUARTZ: Inhalation of very high concentrations of finely divided crystalline silica dust, exposure ranging from a few weeks to 4-5 years, may cause a rapidly developing silicosis, characterized by pulmonary insufficiency with severe dyspnea, violent coughing, tachypnea, weight loss, and cyanosis leading to the development of cor pulmonale and death within a relatively short period of time. A slowly developing silicosis may result from exposure for 6 months-30 years to relatively low levels of the dust. The first symptom is usually a slowly increasing, non-disabling, exertional dyspnea due to pulmonary fibrosis and the emphysema associated with it. Continued exposure may increase the rate of progression of the disease. Also, the fibrogenic action may continue when exposure ceases. As the fibrosis advances, other symptoms may include shortness of breath, productive cough, wheezing, chest tightness or pain, marked weakness, decreased capacity for work, and repeated non-specific chest illnesses. Cyanosis, clubbing of digits, orthopnea, or serious weight loss are not usually evident until the disease is advanced. Pulmonary infections, which may be indicated by hemoptysis, and cardiac decompensation may exacerbate the symptoms. Three major complications, which are the most frequent causes of death, are pulmonary tuberculosis, respiratory insufficiency which is due to the massive emphysematous and fibrotic changes and is sometimes accompanied by chronic cor pulmonale, and acute bronchopulmonary infection. A number of studies have shown that persons diagnosed as having silicosis have an increased risk for dying from lung cancer. This increase has been seen among miners, quarry workers, foundry workers, ceramic workers, granite workers, and stone cutters. In some of these studies, the risk of lung cancer increased with the duration of employment. Various forms and preparations of crystalline silica produced adenocarcinomas and squamous cell carcinomas of the lungs in rats.

SKIN CONTACT:

ACUTE EXPOSURE:

CALCINED ANTHRACITE COAL: No data available.

QUARTZ: May cause irritation of intact skin due to mechanical abrasion. If the skin is abraded, a heavy growth of scar tissue may be induced.

CHRONIC EXPOSURE:

CALCINED ANTHRACITE COAL: No data available.

QUARTZ: No data available.

EYE CONTACT:

ACUTE EXPOSURE:

CALCINED ANTHRACITE COAL: No data available.

QUARTZ: May cause irritation due to mechanical action. Particles of silica in the range of 2-3 micrometers introduced into the corneal stroma of rabbit eyes caused very little reaction. These same particles introduced into the anterior chamber resulted in an inflammatory reaction in 3-5 weeks with the formation of fibrotic nodules in the iridocorneal angle. Finely divided silica injected into the vitreous of rabbit eyes has caused necrosis of the retina and atrophy of the choroid.

CHRONIC EXPOSURE:

CALCINED ANTHRACITE COAL: No data available.

QUARTZ: An abnormally high silicon content in the cornea, and a gradual decrease in visual acuity due to corneal opacities in the pupillary area, have been reported in a group of foundry workers.

INGESTION:

ACUTE EXPOSURE:

CALCINED ANTHRACITE COAL: No data available.

QUARTZ: Effects of ingestion are due to mechanical action as crystalline silicas are biologically inert.

CHRONIC EXPOSURE:

CALCINED ANTHRACITE COAL: No data available.

QUARTZ: No data available.

SECTION 12 ECOLOGICAL INFORMATION

Not available

SECTION 13 DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable regulations.

SECTION 14 TRANSPORT INFORMATION

No classification assigned.

LAND TRANSPORT ADR/RID: No classification assigned.

AIR TRANSPORT IATA/ICAO: No classification assigned.

MARITIME TRANSPORT IMDG: No classification assigned.

SECTION 15 REGULATORY INFORMATION

U.S. REGULATIONS:

TSCA INVENTORY STATUS: Y

TSCA 12(b) EXPORT NOTIFICATION: Not listed.

CERCLA SECTION 103 (40CFR302.4): N

SARA SECTION 302 (40CFR355.30): N

SARA SECTION 304 (40CFR355.40): N

SARA SECTION 313 (40CFR372.65): N

SARA HAZARD CATEGORIES, SARA SECTIONS 311/312 (40CFR370.21):

ACUTE: N

CHRONIC: Y

FIRE: N

REACTIVE: N

SUDDEN RELEASE: N

OSHA PROCESS SAFETY (29CFR1910.119): N

STATE REGULATIONS:

California Proposition 65: Y

Known to the state of California to cause the following:

Silica, crystalline (airborne particles of
respirable size)

Cancer (Oct 01, 1988)

EUROPEAN REGULATIONS:

EC NUMBER (EINECS): 269-111-1

SECTION 16 OTHER INFORMATION

COPYRIGHT 1984-2001 MDL INFORMATION SYSTEMS, INC. ALL RIGHTS RESERVED.

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMETALS
222 Bridge Plaza South
Ft. Lee, NJ 07024

EMERGENCY CONTACT:
CHEMTREC (R)
(800) 424-9300

SUBSTANCE: GRAPHITE, SYNTHETIC

TRADE NAMES/SYNONYMS:
00223639; RTECS MD9659600

CHEMICAL FAMILY: non-metallic

CREATION DATE: Aug 19 1999
REVISION DATE: Mar 22 2001

SECTION 2 COMPOSITION, INFORMATION ON INGREDIENTS

COMPONENT: GRAPHITE, SYNTHETIC
CAS NUMBER: 7782-42-5
EC NUMBER (EINECS): 231-955-3
PERCENTAGE: 100.0

OTHER CONTAMINANTS:
MAY CONTAIN TRACES OF IRON DUST

SECTION 3 HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4): HEALTH=1 FIRE=1 REACTIVITY=0

EMERGENCY OVERVIEW:

PHYSICAL FORM: flakes, crystals, powder

ODOR: odorless

MAJOR HEALTH HAZARDS: No significant target effects reported.

PHYSICAL HAZARDS: Electrostatic charges may be generated by flow, agitation,
etc. Dust/air mixtures may ignite or explode.

POTENTIAL HEALTH EFFECTS:

INHALATION:

SHORT TERM EXPOSURE: no information on significant adverse effects

LONG TERM EXPOSURE: difficulty breathing, lung damage

SKIN CONTACT:

SHORT TERM EXPOSURE: no information on significant adverse effects

LONG TERM EXPOSURE: no information is available

EYE CONTACT:

SHORT TERM EXPOSURE: mechanical irritation

LONG TERM EXPOSURE: no information is available

INGESTION:

SHORT TERM EXPOSURE: no information is available

LONG TERM EXPOSURE: no information is available

CARCINOGEN STATUS:

OSHA: No

NTP: No

IARC: No

SECTION 4 FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.

SKIN CONTACT: Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

EYE CONTACT: Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

INGESTION: If a large amount is swallowed, get medical attention.

SECTION 5 FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Slight fire hazard. Dust/air mixtures may ignite or explode. Dust/air mixtures may ignite or explode. Electrostatic charges may be generated by flow, agitation, etc.

EXTINGUISHING MEDIA: regular dry chemical, carbon dioxide, water, regular foam

Large fires: Use regular foam or flood with fine water spray.

FIRE FIGHTING: Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Dike for later disposal. Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

SECTION 6 ACCIDENTAL RELEASE MEASURES

OCCUPATIONAL RELEASE:

Collect spilled material in appropriate container for disposal. Keep out of water supplies and sewers. Keep unnecessary people away, isolate hazard area and deny entry.

SECTION 7 HANDLING AND STORAGE

STORAGE: Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances.

HANDLING: Use methods to minimize dust.

SECTION 8 EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE LIMITS:

GRAPHITE, SYNTHETIC:

5 mg/m³ OSHA TWA (respirable dust fraction)

15 mg/m³ OSHA TWA (total dust)

10 mg/m³ OSHA TWA (total particulate) (vacated by 58 FR 35338, June 30, 1993)

2 mg/m³ ACGIH TWA (respirable particulate) (all forms except graphite fibers)

1.5 mg/m³ DFG MAK (respirable dust fraction)

MEASUREMENT METHOD: Particulate filter; Gravimetric; NIOSH IV # 0500, Nuisance Dust (total), # 0600 (respirable)

VENTILATION: Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

EYE PROTECTION: Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

CLOTHING: Protective clothing is not required under normal conditions.

GLOVES: Protective gloves are not required, but recommended.

RESPIRATOR: Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Respiratory protection is ranked in order from minimum to maximum. Consider warning properties before use.

Any dust, mist, and fume respirator.

Any air-purifying respirator with a high-efficiency particulate filter.

Any powered, air-purifying respirator with a dust, mist, and fume filter.

Any powered, air-purifying respirator with a high-efficiency particulate filter.

For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.

Any self-contained breathing apparatus with a full facepiece.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: solid

APPEARANCE: lustrous

TEXTURE: oily

PHYSICAL FORM: flakes, crystals, powder

ODOR: odorless

MOLECULAR WEIGHT: 12.01

MOLECULAR FORMULA: C
BOILING POINT: 7592 F (4200 C)
MELTING POINT: Not available
VAPOR PRESSURE: @ 20 C (negligible)
VAPOR DENSITY: Not applicable
SPECIFIC GRAVITY (water=1): 2.09-2.25
WATER SOLUBILITY: insoluble
PH: Not applicable
VOLATILITY: Not applicable
ODOR THRESHOLD: Not available
EVAPORATION RATE: Not applicable
COEFFICIENT OF WATER/OIL DISTRIBUTION: Not available
SOLVENT SOLUBILITY:
Soluble: liquid iron
Insoluble: acids, alkali

SECTION 10 STABILITY AND REACTIVITY

REACTIVITY: Stable at normal temperatures and pressure.

CONDITIONS TO AVOID: Avoid heat, flames, sparks and other sources of ignition.
Avoid contact with incompatible materials.

INCOMPATIBILITIES: halogens, oxidizing materials, metals, bases, metal oxides

GRAPHITE, SYNTHETIC:

CHLORINE TRIFLUORIDE: Ignition.

FLUORINE: Ignition.

OXIDIZERS (STRONG): Fire and explosion hazard.

POTASSIUM (BURNING): Violent explosion.

POTASSIUM (LIQUID): Vigorous reaction.

POTASSIUM PEROXIDE: Fire and explosion hazard.

POTASSIUM SUPEROXIDE: Fire and explosion hazard.

HAZARDOUS DECOMPOSITION:

Thermal decomposition products: oxides of carbon

POLYMERIZATION: Will not polymerize.

SECTION 11 TOXICOLOGICAL INFORMATION

GRAPHITE, SYNTHETIC:

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: respiratory disorders, skin disorders and allergies

HEALTH EFFECTS:

INHALATION:

ACUTE EXPOSURE:

GRAPHITE, SYNTHETIC: Rats exposed to 500 mg/m³ experienced transient inflammation and alveolar macrophage activation for about 24-48 hours following exposure. Excessive concentrations of nuisance dusts in the

workroom may cause unpleasant deposits in the nasal passages.

CHRONIC EXPOSURE:

GRAPHITE, SYNTHETIC: Some evidence suggests that simple and complicated pneumoconiosis similar to that seen in coal workers may occur with repeated exposure. A worker exposed to synthetic graphite dust for 17 years, developed simple pneumoconiosis with cough, dyspnea, reduced pulmonary function, and X-ray changes. At autopsy, there was emphysema with scattered fine black nodules with some strands of fibrous tissue and ventricle hypertrophy.

SKIN CONTACT:

ACUTE EXPOSURE:

GRAPHITE, SYNTHETIC: Allergic dermatitis has been reported. Excessive concentration of nuisance dusts in the workroom may cause unpleasant deposits on the skin and in the ears. Injury to the skin may occur by chemical or mechanical action or by the vigorous skin cleansing procedures necessary for their removal.

CHRONIC EXPOSURE:

GRAPHITE, SYNTHETIC: No data available.

EYE CONTACT:

ACUTE EXPOSURE:

GRAPHITE, SYNTHETIC: Graphite is chemically inert but acts as a superficial foreign body and may cause slight mechanical irritation and discoloration of lids and conjunctivae.

CHRONIC EXPOSURE:

GRAPHITE, SYNTHETIC: No data available.

INGESTION:

ACUTE EXPOSURE:

GRAPHITE, SYNTHETIC: No data available.

CHRONIC EXPOSURE:

GRAPHITE, SYNTHETIC: No data available.

SECTION 12 ECOLOGICAL INFORMATION

Not available

SECTION 13 DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable regulations.

SECTION 14 TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION: No classification assigned.

CANADIAN TRANSPORTATION OF DANGEROUS GOODS: No classification assigned.

LAND TRANSPORT ADR/RID: No classification assigned.

AIR TRANSPORT IATA/ICAO: No classification assigned.

MARITIME TRANSPORT IMDG: No classification assigned.

SECTION 15 REGULATORY INFORMATION

U.S. REGULATIONS:

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4): Not regulated.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30):
Not regulated.

SARA TITLE III SECTION 304 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.40):
Not regulated.

SARA TITLE III SARA SECTIONS 311/312 HAZARDOUS CATEGORIES (40 CFR 370.21):
ACUTE: Yes
CHRONIC: No
FIRE: No
REACTIVE: No
SUDDEN RELEASE: No

SARA TITLE III SECTION 313 (40 CFR 372.65): Not regulated.

OSHA PROCESS SAFETY (29CFR1910.119): Not regulated.

STATE REGULATIONS:

California Proposition 65: Not regulated.

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION: Not determined.

EUROPEAN REGULATIONS:

EC CLASSIFICATION (CALCULATED): Not determined.

GERMAN REGULATIONS:

WATER HAZARD CLASS (WGK):
STATE OF CLASSIFICATION: VwVwS
CLASSIFICATION UNDER HAZARD TO WATER: 0

NATIONAL INVENTORY STATUS:

U.S. INVENTORY (TSCA): Listed on inventory.

TSCA 12(b) EXPORT NOTIFICATION: Not listed.

SECTION 16 OTHER INFORMATION

Copyright 1984-2001 MDL Information Systems, Inc. All rights reserved.

THIS MATERIAL SAFETY DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION & INVESTIGATION. COMETALS PROVIDES NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE DATA CONTAINED HEREIN.